




 IP55 IK10<sup>++</sup> CLASS I 850° C E

# ALEANE LED

An extra low profile, vandal and rip-out resistant, architectural luminaire with anti-graffiti protection.

Also available with asymmetrical light distribution making it ideal for pits.

# ALEANE LED


## FEATURES & BENEFITS

- > High impact resistance: IK10++ / 80 joules
- > Anti-graffiti protection
- > Individual or continuous mounting
- > Non-corrosive
- > Optimum colour consistency—3 step MacAdam ellipse tolerance
- > Average rated LED life: >50,000hrs (L90/B50)
- > Photobiological hazard: RG0



## PERFORMANCE

Light source	LED
Distribution	Symmetric / Asymmetric
Luminaire output	2000 - 7600lm (SYM) 1300 - 2900lm (ASYM)
Luminaire efficiency	≥107lm/W (SYM) ≥71lm/W (ASYM)
CRI	>80



## MATERIALS

Body	Zinc-plated steel
Finish	White (RAL 9003)
Diffuser	Opal polycarbonate TP(a)
External fixings	M6 stainless steel tamper-proof screws
Wiring	3x Ø20.5mm - Fixings outside the sealed body



## OPTIONS

- > Class II version
- > 316L stainless steel version for marine environments
- > Blank infill sections for running cables and through-wiring

LAMP	COLOUR TEMP	DELIVERED LUMENS	DISTRIBUTION	DIMENSIONS	STANDARD	DALI
17W	4000K	2000lm	Symmetric	715 x 270	72500201	72500203
41W	4000K	4400lm	Symmetric	715 x 270	72500401	72500403
41W	4000K	4600lm	Symmetric	1325 x 270	72500601	72500603
70W	4000K	7600lm	Symmetric	1325 x 270	72500801	72500803
17W	4000K	1300lm	Asymmetric	1325 x 290	72501001	72501003
41W	4000K	2900lm	Asymmetric	1325 x 290	72501201	72501203