



IP65 IK08 CLASS I CE

AMAROK IP SURFACE LED

A surface mounted, high efficiency LED luminaire suitable for clean rooms, hospital treatment rooms and any clean environment that needs to be washed down.

AMAROK IP SURFACE LED

FEATURES & BENEFITS

- > High visual comfort - low glare
- > Average rated LED life: 50,000hrs (L80/B10)
- > Optimum colour consistency - 2 step MacAdam ellipse tolerance
- > High anti-bacterial protection
- > Various nominal sizes available: 300 x 600/600 x 600/300 x 1200/600 x 1200
- > Photobiological hazard: RGO

PERFORMANCE



Light source	LED
LED output	2700 - 10800lm
Luminaire output	2036 - 8143lm
Luminaire efficiency	≥107lm/W
CRI	>80
UGR	<19

MATERIALS

Body	Sheet steel
Finish	White
Diffuser	Microprism with tempered anti-reflective glass

OPTIONS

- > 3000K
- > Microwave sensor
- > Other lumen outputs available
- > Internal fuse and LSOH cable



LAMP	COLOUR TEMP	DELIVERED LUMENS	DIMENSIONS	STANDARD	DALI	EMERGENCY	
						STANDARD	DALI
19W	4000K	2036lm	610 x 310	20800201	20800203	20800291	20800293
36W	4000K	4072lm	620 x 620	20800401	20800403	20800491	20800493
36W	4000K	4072lm	1210 x 310	20800601	20800603	20800691	20800693
71W	4000K	8143lm	1210 x 620	20800801	20800803	20800891	20800893