

ASPEN LED

IP65 IK07 CLASS I CE


FEATURES & BENEFITS

- > Compact design
- > High resistance to UV and oxidation
- > Average rated LED life >50,000h (L80/B10)
- > Optimum colour consistency - 3 step MacAdam chromaticity tolerance
- > Light can be directed up or down making it ideal for lighting facades in small environments





PERFORMANCE

Light source	LED
Distribution	Symmetric
LED output	650 - 1425lm
Luminaire output	483 - 702lm
CRI	>85
Beam angle	29° (8W) 26° / 42° (15W)
Swivel	40° - 90°



MATERIALS

Body	Die-cast aluminium
Finish	Anthracite grey / Light grey
Diffuser	4mm soda lime tempered clear glass
Mounting	U-bracket
External fixings	Stainless steel A4-70



OPTIONS

- > DALI
- > Coloured films
- > 200 x 200mm version, 19W
- > Spike

LAMP	COLOUR TEMP	LUMENS	DIMENSIONS	BEAM	ANTHRACITE GREY	LIGHT GREY
8W	3000K	483lm	90 x 90	29°	72100101	72100201
8W	4000K	505lm	90 x 90	29°	72100301	72100401
15W	3000K	584lm	125 x 125	16°	72100501	72100601
15W	4000K	617lm	125 x 125	16°	72100701	72100801
15W	3000K	665lm	125 x 125	42°	72100901	72101001
15W	4000K	702lm	125 x 125	42°	72101101	72101201