

ASPRILLA LED

IP66

IK10

CLASS
II

C E

A high-performance LED floodlight with excellent technical parameters to suit various architectural environments.

FEATURES & BENEFITS

- > Various lumen outputs
- > Long LED life - 80,000hrs (L90/B10)
- > Symmetric and asymmetric lens options
- > NTC thermal sensor to maintain stability
- > Supplied with vent filter as standard
- > Thoughtful design for easy installation
- > Surge protection
- > Photobiological hazard: RG0
- > Tilt angle 180°

PERFORMANCE




Light source	LED (Philips)
Distribution	Symmetric (no lens) Asymmetric (lens with vertex at 50°)
LED output	20800 - 46800lm
Luminaire output	19035 - 42825lm (SYM) 18235 - 41030 (ASYM)
Luminaire efficiency	≥130lm/W
CRI	>80

MATERIALS

Body	Die-cast aluminium
Finish	Anthracite grey (RAL 7039)
Diffuser	4mm tempered glass
Bracket	Steel, 3mm thick

OPTIONS

- > DALI
- > 3000K
- > Additional optics
- > Customised outputs



ASPRILLA LED

LAMP	COLOUR TEMP	DELIVERED LUMENS	OPTIC	STANDARD	DALI
140W	4000K	19035lm	Symmetric	75401501	75401503
175W	4000K	23790lm	Symmetric	75401601	75401603
210W	4000K	28550lm	Symmetric	75401701	75401703
245W	4000K	33310lm	Symmetric	75401801	75401803
280W	4000K	38070lm	Symmetric	75401901	75401903
315W	4000K	42825lm	Symmetric	75402001	75402003
140W	4000K	18235lm	Asymmetric	75402101	75402103
175W	4000K	22795lm	Asymmetric	75402201	75402203
210W	4000K	27350lm	Asymmetric	75402301	75402303
245W	4000K	31910lm	Asymmetric	75402401	75402403
280W	4000K	36470lm	Asymmetric	75402501	75402503
315W	4000K	41030lm	Asymmetric	75402601	75402603



Stainless steel security fixing nut.



Easy access to wiring compartment.