



IP20 IK04 CLASS I CE

ASTON LED

A modern, linear, surface or suspended LED luminaire providing direct or direct and indirect illumination.

Designed for individual or continuous mounting, the Aston LED is ideal for a wide range of environments.

ASTON LED


FEATURES & BENEFITS

- > Modern design
- > Individual or continuous mounting
- > Average rated LED life: >60,000hrs (L80/B10)
- > Optimum colour consistency - 3 step MacAdam chromaticity tolerance



PERFORMANCE

Light source	LED
Emission	Direct / Direct & Indirect
LED output	4712 - 9424lm (DIR) 7496 - 14136lm (DI-IN)
Luminaire output	3510 - 7023lm (DIR) 5288 - 9950lm (DI-IN)
Luminaire efficiency	≥102lm/W (DIR) / ≥105lm/W (DI-IN)
CRI	>80



MATERIALS

Body	Sheet steel
Finish	Grey / White
Diffuser	Opal PMMA
Mounting	Surface or suspension (up to 1.6m)

OPTIONS

- > 3hr emergency
- > 3000K
- > Microprism diffuser, UGR <19
- > Infill sections
- > Internal fuse and LSOH cables



LAMP	COLOUR TEMP	DIRECT LUMENS	INDIRECT LUMENS	GREY		WHITE	
				STANDARD	DALI	STANDARD	DALI
32W	4000K	3510lm	N/A	62316601	62316603	62318401	62318403
36W	4000K	4149lm	N/A	62316801	62316803	62318601	62318603
62W	4000K	7023lm	N/A	62317001	62317003	62318801	62318803
50W	4000K	3305lm	1983lm	62317201	62317203	62319001	62319003
54W	4000K	3880lm	1935lm	62317401	62317403	62319201	62319203
80W	4000K	6562lm	1976lm	62317601	62317603	62319401	62319403
62W	4000K	3330lm	3209lm	62317801	62317803	62319601	62319603
68W	4000K	3880lm	3300lm	62318001	62318003	62319801	62319803
93W	4000K	6714lm	3236lm	62318201	62318203	62320001	62320003