

ATECA LED

IP44

CLASS II

CE


FEATURES & BENEFITS

- > High visual comfort - low glare
- > Long average LED life: >50,000hrs (L80/B10)
- > Optimum colour consistency - 3 step MacAdam chromaticity tolerance



PERFORMANCE

Light source	LED
LED output	937 - 4898lm
Luminaire output	871 - 4033lm
Luminous efficiency	≥87lm/W
CRI	80
UGR	<19
Beam angle	60 degrees



33W, 3000K

MATERIALS

Body	Sheet steel
Bezel	Die-cast aluminium
Finish	White
Diffuser	Clear PMMA
Cut out	Ø75 / 95 / 120 / 145 / 200

OPTIONS

- > 3hr emergency
- > Other RAL colours and beam angles on request



Ø82/105/130/
160/225



LAMP	COLOUR TEMP	DELIVERED LUMENS	DIMENSIONS	STANDARD	DALI	EMERGENCY	
						STANDARD	DALI
10W	3000K	871lm	Ø82 x 75	30100101	30100103	30100191	30100193
10W	4000K	915lm	Ø82 x 75	30100201	30100203	30100291	30100293
15W	3000K	1531lm	Ø105 x 94	30100301	30100303	30100391	30100393
15W	4000K	1615lm	Ø105 x 94	30100401	30100403	30100491	30100493
22W	3000K	2090lm	Ø130 x 97	30100501	30100503	30100591	30100593
22W	4000K	2200lm	Ø130 x 97	30100601	30100603	30100691	30100693
33W	3000K	2527lm	Ø160 x 127	30100701	30100703	30100791	30100793
33W	4000K	2909lm	Ø160 x 127	30100801	30100803	30100891	30100893
30W	3000K	2553lm	Ø225 x 145	30100901	30100903	30100991	30100993
30W	4000K	2910lm	Ø225 x 145	30101001	30101003	30101091	30101093
40W	3000K	3632lm	Ø225 x 145	30101101	30101103	30101191	30101193
40W	4000K	4033lm	Ø225 x 145	30101201	30101203	30101291	30101293