

## CAPRICE IP LED

IP65 IK08 CLASS I CE


## FEATURES &amp; BENEFITS

- > Fully LG7 compliant
- > Average rated LED life: >60,000hrs - (L80/B10)
- > High visual comfort - low glare
- > Optimum colour consistency - 3 step MacAdam ellipse tolerance
- > IP65 at the front and rear of luminaire
- > Photobiological hazard: RG0



## PERFORMANCE

Light source	LED
Emission	Direct & Indirect
LED output	3810 - 7068lm
Luminaire output	2713 - 5032lm
Luminaire efficiency	≥100lm/W
CRI	>80
UGR	<19




## MATERIALS

Body	Sheet steel
Finish	White
Diffuser	Tempered glass

## OPTIONS

- > 2 step MacAdam, CRI >90
- > Internal fuse and LSOH cable



LAMP	COLOUR TEMP	DELIVERED LUMENS	DIMENSIONS	STANDARD	DALI	EMERGENCY STANDARD	DALI
27W	3000K	2713lm	596 x 596	13300101	13300103	13300191	13300193
26W	4000K	2973lm	596 x 596	13300201	13300203	13300291	13300293
47W	3000K	4701lm	596 x 596	13300301	13300303	13300391	13300393
46W	4000K	5032lm	596 x 596	13300401	13300403	13300491	13300493