



IP20 IK04 CLASS I CE

CAPRICE LED

A high output, lay-in modular 600x600 LED luminaire with central flush basket and microprism diffuser providing uniform direct and indirect light distribution.

Suitable for schools, offices, libraries and other public areas.

CAPRICE LED

FEATURES & BENEFITS

- > Microprism diffuser with light transparency $\geq 90\%$
- > Fully LG7 compliant
- > Average rated LED life: >60,000hrs - (L80/B10)
- > High visual comfort - low glare
- > Optimum colour consistency - 3 step MacAdam ellipse tolerance
- > Photobiological hazard: RG0

PERFORMANCE



Light source	LED
Emission	Direct & Indirect
LED output	2540 - 9424lm
Luminaire output	1929 - 7360lm
Luminaire efficiency	$\geq 104\text{lm/W}$
CRI	>80
UGR	<19

MATERIALS

Body	Sheet steel
Finish	White
Diffuser	Microprism TP(a)

OPTIONS

- > 2 step MacAdam, CRI >90
- > Tuneable white
- > Internal fuse and LSOH cable
- > Parabolic louvre



LAMP	COLOUR TEMP	DELIVERED LUMENS	DIMENSIONS	STANDARD	DALI	EMERGENCY	
						STANDARD	DALI
18W	3000K	1929lm	596 x 596	10700501	10700503	10700591	10700593
18W	4000K	2114lm	596 x 596	10700601	10700603	10700691	10700693
32W	3000K	3343lm	596 x 596	10700901	10700903	10700991	10700993
32W	4000K	3578lm	596 x 596	10701001	10701003	10701091	10701093
45W	3000K	5018lm	596 x 596	10701101	10701103	10701191	10701193
45W	4000K	5404lm	596 x 596	10701201	10701203	10701291	10701293
32W	3000K	3343lm	296 x 1196	10701301	10701303	10701391	10701393
32W	4000K	3578lm	296 x 1196	10701401	10701403	10701491	10701493
62W	3000K	6876lm	296 x 1196	10701501	10701503	10701591	10701593
62W	4000K	7360lm	296 x 1196	10701601	10701603	10701691	10701693