



IP20 IK04 CLASS I CE

CAYENNE LED

A multi-directional, low bay LED luminaire available in a narrow and wide range of light distribution.

Ideal for aisle lighting in warehouses as well as industrial and retail environments.

CAYENNE LED


FEATURES & BENEFITS

- > Maximum design flexibility - symmetric or asymmetric light distribution
- > Long rated LED life: >60,000hrs (L90/B10)
- > Optimum colour consistency—3 step MacAdam ellipse tolerance



PERFORMANCE

Light source	LED
Emission	Direct
Distribution	Symmetric/Asymmetric
LED output	5568 - 13920lm (SYM) 2784 - 7068lm (ASYM)
Luminaire output	4451 - 11126 (SYM) 2223 - 5644 (ASYM)
Luminaire efficiency	≥ 118lm/W
CRI	>80




Asymmetric 18W, 4000K

MATERIALS

Body	Sheet steel
Finish	White
Diffuser	Microprism
Mounting	Surface/suspended

OPTIONS

- > 3hr emergency
- > 3000K
- > Internal fuse and LSOH cables



LAMP	COLOUR TEMP	DELIVERED LUMENS	DISTRIBUTION	DIMENSIONS	STANDARD	DALI
36W	4000K	4451lm	Symmetric	1111 x 162 x 75	60501801	60501803
54W	4000K	6676lm	Symmetric	1673 x 162 x 75	60502001	60502003
62W	4000K	7533lm	Symmetric	1111 x 162 x 75	60502201	60502203
90W	4000K	11126lm	Symmetric	1673 x 162 x 75	60502401	60502403
18W	4000K	2223lm	Asymmetric	1111 x 162 x 75	60502601	60502603
27W	4000K	3335lm	Asymmetric	1673 x 162 x 75	60502801	60502803
32W	4000K	3763lm	Asymmetric	1111 x 162 x 75	60503001	60503003
47W	4000K	5644lm	Asymmetric	1673 x 162 x 75	60503201	60503203