

## CENTRO LED

IP44

CLASS  
II

C E

## FEATURES &amp; BENEFITS

- > Fully LG7 compliant
- > High visual comfort - low glare and zero flicker
- > Average rated LED life: >50,000hrs (L80/B10)
- > Optimum colour consistency - 3 step MacAdam chromaticity tolerance



## PERFORMANCE



Light source	LED
Luminaire output	2820 - 8657lm
Luminaire efficiency	≥102lm/W
CRI	>80
UGR	<19

## MATERIALS

Body	Sheet steel
Finish	White
Diffuser	Microprism centre, satin opal sides

## OPTIONS

- > Other RAL finishes
- > Internal fuse and LSOH cable



LAMP	COLOUR TEMP	DELIVERED LUMENS	DIMENSIONS	STANDARD	DALI	EMERGENCY STANDARD	DALI
25W	3000K	2820lm	595 x 595 x 65	13600101	13600103	13600191	13600193
25W	4000K	2984lm	595 x 595 x 65	13600201	13600203	13600291	13600293
32W	3000K	3542lm	595 x 595 x 65	13600301	13600303	13600391	13600393
32W	4000K	3749lm	595 x 595 x 65	13600401	13600403	13600491	13600493
38W	3000K	4092lm	595 x 595 x 65	13600501	13600503	13600591	13600593
38W	4000K	4329lm	595 x 595 x 65	13600601	13600603	13600691	13600693
52W	3000K	5304lm	595 x 595 x 65	13600701	13600703	13600791	13600793
52W	4000K	5594lm	595 x 595 x 65	13600801	13600803	13600891	13600893
38W	3000K	4069lm	295 x 1195 x 65	13600901	13600903	13600991	13600993
38W	4000K	4329lm	295 x 1195 x 65	13601001	13601003	13601091	13601093
76W	3000K	8138lm	295 x 1195 x 65	13601101	13601103	13601191	13601193
76W	4000K	8657lm	295 x 1195 x 65	13601201	13601203	13601291	13601293