


FEATURES & BENEFITS

- > Attractive modern design
- > Homogenous light distribution - no spotting
- > Optimum colour consistency - 3 step MacAdam ellipse tolerance
- > Long rated LED life: >72,000hrs (L80/B10)



PERFORMANCE

Light source	LED
Luminaire output	1700 - 12250lm
CRI	83
Beam angle	110°




MATERIALS

Body	Aluminium profile
Finish	Grey
Diffuser	Opal PMMA

OPTIONS

- > Other RAL colours available
- > Suspension kit (1.5m standard length)
- > Microprism diffuser
- > Bluetooth enabled
- > Internal fuse and LSOH cable

66 / 110 |



Ø320 / 440 / 520 / 630 / 800 / 1065

LAMP	COLOUR TEMP	DELIVERED LUMENS	DIMENSIONS	STANDARD	DALI	EMERGENCY	
						STANDARD	DALI
16W	3000K	1700lm	Ø320 x 66	60608601	60608603	60608691	60608693
16W	4000K	1750lm	Ø320 x 66	60608701	60608703	60608791	60608793
37W	3000K	3760lm	Ø440 x 66	60608801	60608803	60608891	60608893
37W	4000K	3870lm	Ø440 x 66	60608901	60608903	60608991	60608993
37W	3000K	4030lm	Ø520 x 66	60609001	60609003	60609091	60609093
37W	4000K	4150lm	Ø520 x 66	60609101	60609103	60609191	60609193
37W	3000K	4400lm	Ø630 x 110	60609201	60609203	60609291	60609293
37W	4000K	4530lm	Ø630 x 110	60609301	60609303	60609391	60609393
57W	3000K	6180lm	Ø800 x 110	60609401	60609403	60609491	60609493
57W	4000K	6370lm	Ø800 x 110	60609501	60609503	60609591	60609593
100W	3000K	11880lm	Ø1065 x 110	60609601	60609603	60609691	60609693
100W	4000K	12250lm	Ø1065 x 110	60609701	60609703	60609791	60609793