

# CRUZE LED

IP44

IK07

CLASS I

CE

SECTION 02: LINEAR

## FEATURES & BENEFITS

- > Uniform, diffuse illumination
- > High visual comfort
- > Average rated LED life: >50,000hrs (L80/B10)
- > Optimum colour consistency - 3 step MacAdam chromaticity tolerance



## PERFORMANCE



Light source	LED
Emission	Direct
Luminaire output	3350 - 8450lm
Luminaire efficiency	≥ 105lm/W
CRI	>80

## MATERIALS

Body	Sheet steel
Finish	White (RAL 9016)
Diffuser	Opal prismatic TP(a)
Mounting	Surface

## OPTIONS

- > 3hr emergency
- > 3000K
- > Through-wiring
- > Microwave sensor for enhanced energy saving



LAMP	COLOUR TEMP	DELIVERED LUMENS	LENGTH	STANDARD	DALI	EMERGENCY	
						STANDARD	DALI
28W	4000K	3350lm	601mm	25901201	25901203	25901291	25901293
27W	4000K	3500lm	1161mm	25901401	25901403	25901491	25901493
50W	4000K	6050lm	1161mm	25901601	25901603	25901691	25901693
48W	4000K	6100lm	1441mm	25901801	25901803	25901891	25901893
71W	4000K	8450lm	1441mm	25902001	25902003	25902091	25902093

www.spearlighting.com | T: 01895 746006 | F: 01895 746005