

IP54

IK10

CLASS  
I

C E

# DELIA LED

A contemporary, stylish surface mounted luminaire available in various lumen outputs and sizes along with a complementary pendant luminaire. Ideal for reception areas, meeting rooms, showrooms and restaurants.

# DELIA LED

## FEATURES & BENEFITS

- > Modern design
- > Available in various lumen outputs and sizes for design flexibility
- > Long rated LED life: >67,000hrs (L80/B10)
- > Optimum colour consistency - 3 step MacAdam chromaticity tolerance

## PERFORMANCE


Light source	LED (Samsung)
LED output	2000 - 23170lm
Luminaire output	1480 - 16220lm
Luminaire efficiency	≥95lm/W
CRI	>80
Beam angle	110°

## MATERIALS


Body	Sheet steel
Finish	White
Diffuser	Opal polycarbonate (∅300/400/500) PMMA (∅650 / 900)

## OPTIONS

- > Microwave sensor for enhanced energy savings
- > Complementary pendant
- > Bluetooth control
- > Replacement shade



∅300/400/500/650/900



75/80/85



LAMP	COLOUR TEMP	DELIVERED LUMENS	DIMENSIONS	STANDARD	DALI	EMERGENCY STANDARD	DALI
14W	3000K	1480lm	Ø300x75	42100101	42100103	42100191	42100193
14W	4000K	1560lm	Ø300x75	42100201	42100203	42100291	42100293
19W	3000K	1920lm	Ø300x75	42100301	42100303	42100391	42100393
19W	4000K	2000lm	Ø300x75	42100401	42100403	42100491	42100493
27W	3000K	2580lm	Ø400x80	42100501	42100503	42100591	42100593
27W	4000K	2720lm	Ø400x80	42100601	42100603	42100691	42100693
33W	3000K	3400lm	Ø400x80	42100701	42100703	42100791	42100793
33W	4000K	3550lm	Ø400x80	42100801	42100803	42100891	42100893
33W	3000K	3140lm	Ø500x85	42100901	42100903	42100991	42100993
33W	4000K	3310lm	Ø500x85	42101001	42101003	42101091	42101093
49W	3000K	4470lm	Ø500x85	42101101	42101103	42101191	42101193
49W	4000K	4720lm	Ø500x85	42101201	42101203	42101291	42101293
64W	3000K	6940lm	Ø650x80	42101301	42101303	42101391	42101393
64W	4000K	7260lm	Ø650x80	42101401	42101403	42101491	42101493
100W	3000K	10060lm	Ø650x80	42101501	42101503	42101591	42101593
100W	4000K	10510lm	Ø650x80	42101601	42101603	42101691	42101693
98W	3000K	10720lm	Ø900x85	42101701	42101703	42101791	42101793
98W	4000K	11200lm	Ø900x85	42101801	42101803	42101891	42101893
150W	3000K	15530lm	Ø900x85	42101901	42101903	42101991	42101993
150W	4000K	16220lm	Ø900x85	42102001	42102003	42102091	42102093