

EMG TRACK

IP20 CLASS I CE

A flexible, self-contained three circuit track mounted solution for LED emergency applications.

FEATURES & BENEFITS

- > 3hr non-maintained emergency operation
- > Avoids the need for separate emergency lighting
- > Energy efficient LED light source - long lamp life
- > Eutrac or Global Track compatible



SECTION 10: EMERGENCY

PERFORMANCE

Light source	LED
Battery	3.6V 4.0Ah NiMH
Luminaire output	190lm (max)
Beam angle	60°
CRI	>80
Mains supply current	20mA
Discharge current	375mA
Recharge period	<24hrs

MATERIALS

Housing	Sheet steel
Finish	White / Silver / Black
Mounting	Three circuit track (mechanically locked)

OPTIONS

- > DALI
- > Maintained operation



POWER	COLOUR TEMP	FINISH	BRAND	STANDARD	DALI
3W	6000K	White	Eutrac	81600105	81600103
3W	6000K	Silver	Eutrac	81600205	81600203
3W	6000K	Black	Eutrac	81600305	81600303
3W	6000K	White	Global	81600405	81600403
3W	6000K	Silver	Global	81600505	81600503
3W	6000K	Black	Global	81600605	81600603

www.spearlighting.com | T: 01895 746006 | F: 01895 746005