

EDGE LED

IP20 CLASS I F MARK CE

FEATURES & BENEFITS

- > Suspension or surface mounting
- > Individual or continuous mounting
- > Average rated LED life: >54,000hrs (L90/B10)
- > Optimum colour consistency - 3 step MacAdam chromaticity tolerance
- > High visual comfort




PERFORMANCE

Light source	LED
Emission	Direct
LED output	3340 - 6810lm
Luminaire output	2730 - 5600lm
Lumen efficiency	>113lm/W
CRI	83

MATERIALS

Body	Aluminium profile
Finish	White
Diffuser	Opal polycarbonate TP(a)
End caps	Reinforced polycarbonate



OPTIONS

- > 3hr maintained emergency
- > Other RAL finishes available on request
- > Through-wiring on request
- > Various accessories available - end caps, joining kit and suspension kit
- > Infill sections
- > Internal fuse and LSOH cables



LAMP	COLOUR TEMP	DELIVERED LUMENS	DIMENSIONS	SURFACE		SUSPENDED	
				STANDARD	DALI	STANDARD	DALI
24W	3000K	2730lm	875 x 101	22004101	22004103	22004901	22004903
24W	4000K	2790lm	875 x 101	22004201	22004203	22005001	22005003
31W	3000K	3640lm	1165 x 101	22004301	22004303	22005101	22005103
31W	4000K	3720lm	1165 x 101	22004401	22004403	22005201	22005203
38W	3000K	4570lm	1455 x 101	22004501	22004503	22005301	22005303
38W	4000K	4660lm	1455 x 101	22004601	22004603	22005401	22005403
44W	3000K	5480lm	1745 x 101	22004701	22004703	22005501	22005503
44W	4000K	5600lm	1745 x 101	22004801	22004803	22005601	22005603