

IP65 IK08 CLASS I CE

# ELITE LINE LED

A high performance, energy efficient LED linear industrial high bay luminaire, which is ideally suited to warehouses, halls, production areas and other similar environments.

# ELITE LINE LED

## FEATURES & BENEFITS

- > High powered LED light source
- > Design flexibility - various lumen outputs
- > Average rated LED life: >83,000hrs (L90/B10) - maintenance free
- > Optimum colour consistency - 2 step MacAdam ellipse tolerance

## PERFORMANCE


Light source	LED
Distribution	Direct
LED output	17160 - 34320lm
Luminaire output	12144 - 29831lm
Luminaire efficiency	≥98lm/W
CRI	>80
Beam angle	Narrow / Medium / Wide

## MATERIALS


Body	Aluminium
Finish	Black (RAL 9005)
Diffuser	Tempered glass
Mounting	Surface/Suspended

## OPTIONS

- > Suspension kit
- > Reduced and higher outputs



166W, 4000K, medium beam



449/599/751

LAMP	COLOUR TEMP	DELIVERED LUMENS	BEAM	DIMENSIONS	STANDARD	DALI
125W	4000K	12144lm	Narrow	449x185x160	61103001	61103003
125W	4000K	14246lm	Medium	449x185x160	61103101	61103103
125W	4000K	14915lm	Wide	449x185x160	61103201	61103203
166W	4000K	16192lm	Narrow	449x185x160	61103301	61103303
166W	4000K	18995lm	Medium	449x185x160	61103401	61103403
166W	4000K	19887lm	Wide	449x185x160	61103501	61103503
208W	4000K	20240lm	Narrow	599x185x160	61103601	61103603
208W	4000K	23744lm	Medium	599x185x160	61103701	61103703
208W	4000K	24859lm	Wide	599x185x160	61103801	61103803
249W	4000K	24288lm	Narrow	751x185x160	61103901	61103903
249W	4000K	28492lm	Medium	751x185x160	61104001	61104003
249W	4000K	29831lm	Wide	751x185x160	61104101	61104103