



IP20 CLASS I F MARK CE

# EVOQUE LED

An eye-catching, high quality, decorative LED luminaire defined by its square shape.

Ideal for areas that require “something different”!

# EVOQUE LED

## FEATURES & BENEFITS

- > Recessed or surface mounting
- > Functional yet eye-catching design
- > Homogeneous light distribution
- > Average rated LED life: >54,000hrs (L90/B10)
- > Optimum colour consistency - 3 step MacAdam chromaticity tolerance
- > Photobiological hazard: RG1

## PERFORMANCE



Light source	LED
LED output	6720 - 6840lm
Luminaire output	4280 - 4370lm
Luminaire efficiency	≥112lm/W
CRI	>80

## MATERIALS

Body	Sheet steel
Finish	White
Diffuser	Opal PMMA

## OPTIONS

- > 2 step MacAdam, CRI >90
- > Dual lighting with downlighter
- > Internal fuse and LSOH cable



LAMP	COLOUR TEMP	DELIVERED LUMENS	MOUNTING	STANDARD	DALI	EMERGENCY STANDARD	
						STANDARD	DALI
38W	3000K	4280lm	Recessed	11400901	11400903	11400991	11400993
38W	4000K	4370lm	Recessed	11401001	11401003	11401091	11401093
38W	3000K	4280lm	Surface	11401101	11401103	11401191	11401193
38W	4000K	4370lm	Surface	11401201	11401203	11401291	11401293