

FOCUS RECESSED LED

IP20

CLASS
I

CE

FEATURES & BENEFITS

- > Stunning black pearl reflector for aesthetic appeal
- > High visual comfort - exceptionally low glare
- > Average rated LED life: >50,000hrs (L80/B10)
- > Optimum colour consistency - 3 step MacAdam ellipse tolerance

PERFORMANCE



Light source	LED
Distribution	Symmetric / Asymmetric
Luminaire output	380 - 1707lm (Symmetric) 460—1818lm (Asymmetric)
CRI	90
Beam angle	15° / 24° / 38°
UGR	<19

MATERIALS

Body	Aluminium
Finish	White
Reflector	Black pearl
Mounting	Recessed
Cut out	Ø75 x 95: cut out: Ø65mm Ø95 x 110: cut out: Ø85mm

OPTIONS

- > Larger size (Ø125 x 135) available - 20W / 28W
- > Triac dimming
- > Other RAL colours and 2700K available
- > Champagne gold anti-glare reflector
- > Honeycomb, linear spread lens and spread lens accessories
- > Complementary pendants, wall luminaires, surface downlights and track luminaires



FOCUS RECESSED LED

SYMMETRIC DISTRIBUTION

LAMP	COLOUR TEMP	DELIVERED LUMENS	BEAM	DIMENSIONS	WHITE
7W	3000K	380lm	15°	Ø75 x 95	35201301
7W	4000K	412lm	15°	Ø75 x 95	35201401
7W	3000K	430lm	24°	Ø75 x 95	35201501
7W	4000K	495lm	24°	Ø75 x 95	35201601
7W	3000K	420lm	38°	Ø75 x 95	35201701
7W	4000K	478lm	38°	Ø75 x 95	35201801
10W	3000K	490lm	15°	Ø75 x 95	35201901
10W	4000K	532lm	15°	Ø75 x 95	35202001
10W	3000K	510lm	24°	Ø75 x 95	35202101
10W	4000K	587lm	24°	Ø75 x 95	35202201
10W	3000K	530lm	38°	Ø75 x 95	35202301
10W	4000K	603lm	38°	Ø75 x 95	35202401
15W	3000K	900lm	15°	Ø95 x 110	35202501
15W	4000K	977lm	15°	Ø95 x 110	35202601
15W	3000K	980lm	24°	Ø95 x 110	35202701
15W	4000K	1127lm	24°	Ø95 x 110	35202801
15W	3000K	1100lm	38°	Ø95 x 110	35202901
15W	4000K	1252lm	38°	Ø95 x 110	35203001
20W	3000K	1300lm	15°	Ø95 x 110	35203101
20W	4000K	1411lm	15°	Ø95 x 110	35203201
20W	3000K	1400lm	24°	Ø95 x 110	35203301
20W	4000K	1590lm	24°	Ø95 x 110	35203401
20W	3000K	1500lm	38°	Ø95 x 110	35203501
20W	4000K	1707lm	38°	Ø95 x 110	35203601

ASYMMETRIC / WALL WASH DISTRIBUTION

LAMP	COLOUR TEMP	DELIVERED LUMENS	DISTRIBUTION	DIMENSIONS	WHITE
7W	3000K	460lm	Asymmetric	Ø75 x 95	35200101
7W	4000K	503lm	Asymmetric	Ø75 x 95	35200201
10W	3000K	530lm	Asymmetric	Ø75 x 95	35200301
10W	4000K	580lm	Asymmetric	Ø75 x 95	35200401
15W	3000K	1200lm	Asymmetric	Ø95 x 110	35200501
15W	4000K	1314lm	Asymmetric	Ø95 x 110	35200601
20W	3000K	1660lm	Asymmetric	Ø95 x 110	35200701
20W	4000K	1818lm	Asymmetric	Ø95 x 110	35200801