

GALAXY LED

IP20

CLASS
IF
MARK

C E

FEATURES & BENEFITS

- > High luminaire efficiency
- > Surface or suspension mounting
- > Average rated LED life: >54,000hrs (L90/B10)
- > Optimum colour consistency - 3 step MacAdam chromaticity tolerance




PERFORMANCE

Light source	LED
Emission	Direct
LED output	4020 - 6830lm (Opal) 4050 - 8240lm (Louvre)
Luminaire output	3040 - 5180lm (Opal) 3410 - 6980lm (Louvre)
Luminaire efficiency	≥113lm/W
CRI	>80
UGR	<19 (Louvre)

MATERIALS

Body	Sheet steel
Finish	White
Diffuser	Opal PMMA
Louvre	Polished anodised aluminium
End caps	Reinforced polycarbonate
Mounting	Surface / Suspension



27W, 4000K, Opal

OPTIONS

- > Suspension kit ("Y" type)
- > Other RAL finishes
- > Asymmetrical version
- > Internal fuse and LSOH cables



LAMP	COLOUR TEMP	DELIVERED LUMENS	TYPE	DIMENSIONS	STANDARD	DALI	EMERGENCY	
							STANDARD	DALI
27W	3000K	3040lm	Opal	830x223	60702501	60702503	60702591	60702593
27W	4000K	3100lm	Opal	830x223	60702601	60702603	60702691	60702693
35W	3000K	4060lm	Opal	1080x223	60702701	60702703	60702791	60702793
35W	4000K	4140lm	Opal	1080x223	60702801	60702803	60702891	60702893
42W	3000K	5080lm	Opal	1330x223	60702901	60702903	60702991	60702993
42W	4000K	5180lm	Opal	1330x223	60703001	60703003	60703091	60703093
27W	3000K	3410lm	Louvre	640x223	60703101	60703103	60703191	60703193
27W	4000K	3490lm	Louvre	640x223	60703201	60703203	60703291	60703293
51W	3000K	6830lm	Louvre	1180x223	60703301	60703303	60703391	60703393
51W	4000K	6980lm	Louvre	1180x223	60703401	60703403	60703491	60703493