



IP20 IK04 CLASS I CE

GENESIS LED

A unique, slim, back-lit LED panel with a high photometric performance and a uniform illuminance to fit a lay-in modular or plasterboard ceiling as an option.

GENESIS LED

FEATURES & BENEFITS

- > High lumen efficiency
- > Average rated LED life: >60,000hrs (L80/B10)
- > Optimum colour consistency - 3 step MacAdam chromaticity tolerance
- > Suitable for recessed mounting in modular ceilings
- > Photobiological hazard: RG0

PERFORMANCE



Light source	LED
LED output	2600 - 4400lm
Luminaire output	1911 - 3545lm
Luminaire efficiency	≥100lm/W
CRI	>80

MATERIALS

Body	Sheet steel
Finish	White
Diffuser	Opal PMMA (850°C glow wire tested)

OPTIONS

- > 2 step MacAdam, CRI >90
- > Plasterboard ceiling mounting
- > Higher outputs available
- > Microprismatic diffuser
- > Internal fuse and LSOH cable



LAMP	COLOUR TEMP	DELIVERED LUMENS	STANDARD	DALI	EMERGENCY	
					STANDARD	DALI
19W	3000K	1911lm	11200501	11200503	11200591	11200593
18W	4000K	2094lm	11200601	11200603	11200691	11200693
33W	3000K	3312lm	11200701	11200703	11200791	11200793
32W	4000K	3545lm	11200801	11200803	11200891	11200893