



IP65 IK08 CLASS I CE

GREENLIGHT LED

A multi-functional LED pillar luminaire available in various heights and angles. Ideal for use on pathways, gardens, public and residential areas.

GREENLIGHT LED

FEATURES & BENEFITS

- > Cost effective discreet lighting solution for pathways and gardens
- > High resistance to oxidation
- > Suitable for interior and exterior use
- > Average rated LED life: >50,000hrs (L70/B50)
- > Optimum colour consistency - 3 step MacAdam ellipse tolerance

PERFORMANCE

Light source	LED
Distribution	90° or 115°
LED output	630 - 640lm
Luminaire output	480 - 490lm
CRI	>80

MATERIALS

Body	Aluminium profile treated to resist external conditions
Finish	Anthracite grey
Diffuser	Opal glass
Mounting	Steel, 3mm thick

OPTIONS

- > Other finishes on request
- > Concrete root mounting kit

BOLLARD POLE

HEAD DIMENSIONS	500MM HEIGHT	1000MM HEIGHT
50 x 60	90172701	90172702
50 x 100	90172703	90172704

BOLLARD HEAD

LAMP	COLOUR TEMP	DELIVERED LUMENS	HEAD ANGLE	HEAD DIMENSIONS	STANDARD	DALI
9W	3000K	480lm	115°	50 x 60	72700101	72700103
9W	4000K	490lm	115°	50 x 60	72700201	72700203
9W	3000K	480lm	90°	50 x 100	72700301	72700303
9W	4000K	490lm	90°	50 x 100	72700401	72700403
9W	3000K	480lm	115°	50 x 100	72700501	72700503
9W	4000K	490lm	115°	50 x 100	72700601	72700603

