

IP20 IK04 CLASS I CE

MUSTANG LED

A recessed lay-in modular LED luminaire providing soft, diffuse illumination without any glare.

Suitable for schools, offices, libraries and other public areas.

MUSTANG LED

FEATURES & BENEFITS

- > Microprism diffuser with light transparency $\geq 90\%$
- > Fully LG7 compliant
- > Average rated LED life: $>60,000$ hrs - (L80/B10)
- > High visual comfort - low glare
- > High lumen efficiency ≥ 100 lm/W
- > Optimum colour consistency - 3 step MacAdam ellipse tolerance
- > Photobiological hazard: RG0

PERFORMANCE



Light source	LED
Emission	Direct & Indirect
LED output	5080 - 9424lm
Luminaire output	3274 - 6074lm
Luminaire efficiency	≥ 90 lm/W
CRI	>80
UGR	<19

MATERIALS

Body	Sheet steel
Finish	White
Diffuser	Microprism TP(a)

OPTIONS

- > 2 step MacAdam, CRI >90
- > Internal fuse and LSOH cable



LAMP	COLOUR TEMP	DELIVERED LUMENS	DIMENSIONS	STANDARD	DALI	EMERGENCY STANDARD	DALI
36W	3000K	3274lm	593 x 593	13400101	13400103	13400191	13400193
36W	4000K	3589lm	593 x 593	13400201	13400203	13400291	13400293
62W	3000K	5675lm	593 x 593	13400301	13400303	13400391	13400393
62W	4000K	6074lm	593 x 593	13400401	13400403	13400491	13400493