

# NAVARA LED

IP40	IK10	CLASS I
850 °	CE	

## FEATURES & BENEFITS

- > Multiple lengths and outputs available
- > Easy height adjustment without the need for tools
- > Average rated LED life: >50,000hrs (L80/B10) @ TC=65°C
- > Optimum colour consistency - 3 step MacAdam chromaticity tolerance

## PERFORMANCE



Light source	LED
Emission	Direct / Direct & Indirect
Luminaire output	824 - 2472lm (360°) 2519 - 8029lm (120°)
Luminaire efficiency	≥103lm/W (360°) ≥139lm/W (120°)
CRI	>80
Beam angle	120 degrees / 360 degrees

## MATERIALS

Body	Aluminium
Finish	Matt white
Diffuser	Opal polycarbonate TP(a)
End caps	Aluminium (no visible screws)
Mounting	Stainless steel suspension cable 1m with surface ceiling cup

## OPTIONS

- > 3m and 5m suspension cable
- > Recessed ceiling cup
- > IP65 version
- > Surface mounted version Ø70mm only



# NAVARA LED

LAMP	COLOUR TEMP	DELIVERED LUMENS	DIMENSIONS	BEAM	STANDARD	DALI
8W	3000K	824lm	Ø70 x 574	360°	60104501	60104503
7W	4000K	824lm	Ø70 x 574	360°	60104601	60104603
16W	3000K	1648lm	Ø70 x 1074	360°	60104701	60104703
15W	4000K	1648lm	Ø70 x 1074	360°	60104801	60104803
23W	3000K	2472lm	Ø70 x 1574	360°	60104901	60104903
22W	4000K	2472lm	Ø70 x 1574	360°	60105001	60105003
18W	3000K	2519lm	Ø55 x 900	120°	60105101	60105103
18W	4000K	2624lm	Ø55 x 900	120°	60105201	60105203
17W	3000K	2440lm	Ø55 x 1181	120°	60105301	60105303
17W	4000K	2558lm	Ø55 x 1181	120°	60105401	60105403
24W	3000K	3359lm	Ø55 x 1181	120°	60105501	60105503
24W	4000K	3499lm	Ø55 x 1181	120°	60105601	60105603
21W	3000K	3051lm	Ø55 x 1462	120°	60105701	60105703
21W	4000K	3197lm	Ø55 x 1462	120°	60105801	60105803
30W	3000K	4199lm	Ø55 x 1462	120°	60105901	60105903
30W	4000K	4374lm	Ø55 x 1462	120°	60106001	60106003
34W	3000K	4881lm	Ø55 x 2305	120°	60106101	60106103
34W	4000K	5115lm	Ø55 x 2305	120°	60106201	60106203
48W	3000K	6718lm	Ø55 x 2305	120°	60106301	60106303
48W	4000K	6998lm	Ø55 x 2305	120°	60106401	60106403
20W	3000K	2874lm	Ø70 x 900	120°	60106501	60106503
20W	4000K	3011lm	Ø70 x 900	120°	60106601	60106603
18W	3000K	2655lm	Ø70 x 1181	120°	60106701	60106703
18W	4000K	2782lm	Ø70 x 1181	120°	60106801	60106803
27W	3000K	3832lm	Ø70 x 1181	120°	60106901	60106903
27W	4000K	4015lm	Ø70 x 1181	120°	60107001	60107003
22W	3000K	3319lm	Ø70 x 1462	120°	60107101	60107103
22W	4000K	3477lm	Ø70 x 1462	120°	60107201	60107203
34W	3000K	4790lm	Ø70 x 1462	120°	60107301	60107303
34W	4000K	5018lm	Ø70 x 1462	120°	60107401	60107403
35W	3000K	5311lm	Ø70 x 2305	120°	60107501	60107503
35W	4000K	5563lm	Ø70 x 2305	120°	60107601	60107603
54W	3000K	7665lm	Ø70 x 2305	120°	60107701	60107703
54W	4000K	8029lm	Ø70 x 2305	120°	60107801	60107803