

# NAVARA SURFACE LED



## FEATURES & BENEFITS

- > Average rated LED life: >60,000hrs (L70/B10) @ TC=65°C
- > Optimum colour consistency - 3 step MacAdam chromaticity tolerance
- > Multiple lengths and outputs available

## PERFORMANCE


Light source	LED
Emission	Direct
Luminaire output	2042 - 7116lm
Luminaire efficiency	≥113lm/W
CRI	>80
Beam angle	120 degrees

## MATERIALS

Body	Aluminium
Finish	Anodised aluminium
Diffuser	Opal polycarbonate TP(a)
End caps	ABS plastic
Mounting	Surface brackets with horizontal adjustment

## OPTIONS

- > Suspended version
- > IP65 version
- > Other lumen outputs available



Ø70



868/1149/1430/2273/2835

LAMP	COLOUR TEMP	DELIVERED LUMENS	DIMENSIONS	BEAM	STANDARD	DALI
18W	3000K	2042lm	Ø70 x 868	120°	60102501	60102503
18W	4000K	2136lm	Ø70 x 868	120°	60102601	60102603
24W	3000K	2718lm	Ø70 x 1149	120°	60102901	60102903
24W	4000K	2843lm	Ø70 x 1149	120°	60103001	60103003
30W	3000K	3401lm	Ø70 x 1430	120°	60103301	60103303
30W	4000K	3558lm	Ø70 x 1430	120°	60103401	60103403
47W	3000K	5435lm	Ø70 x 2273	120°	60103701	60103703
47W	4000K	5687lm	Ø70 x 2273	120°	60103801	60103803
59W	3000K	6802lm	Ø70 x 2835	120°	60104101	60104103
59W	4000K	7116lm	Ø70 x 2835	120°	60104201	60104203