



IP65 IK06 CLASS I CE

NEVADA LED

A high powered, wall mounted LED fixture that can be angled to provide upward or downward illumination.

Ideal for the illumination of entrances, passageways, courtyards and gardens.

NEVADA LED

FEATURES & BENEFITS

- > Various lumen outputs up to 6075lm
- > High resistance to UV and oxidation
- > Average rated LED life: >50,000hrs (L80/B10)
- > Optimum colour consistency - 3 step MacAdam ellipse tolerance
- > Uniform light distribution

PERFORMANCE



Light source	LED
Distribution	Symmetric
LED output	3500 - 11250lm
Luminaire output	1890 - 6075lm
Luminaire efficiency	≥85lm/W
CRI	>85

MATERIALS

Body	Extruded aluminium EN AW-6063
Finish	Anthracite grey / Light grey
Diffuser	10mm soda-lime tempered glass with sealing gasket
External fittings	Stainless steel A4-70 treated against oxidation
Wiring	Nickel-plated brass cable gland M16 Ø5.5 /10mm

OPTIONS

- > 3hr emergency



LAMP	COLOUR TEMP	DELIVERED LUMENS	DIMENSIONS	STANDARD		DALI	
				ANTHRACITE GREY	LIGHT GREY	ANTHRACITE GREY	LIGHT GREY
22W	3000K	1890lm	160 x 255 x 133	75900101	75900201	75900103	75900203
22W	4000K	2025lm	160 x 255 x 133	75900301	75900401	75900303	75900403
44W	3000K	3780lm	280 x 255 x 133	75900501	75900601	75900503	75900603
44W	4000K	4050lm	280 x 255 x 133	75900701	75900801	75900703	75900803
66W	3000K	5670lm	400 x 255 x 133	75900901	75901001	75900903	75901003
66W	4000K	6075lm	400 x 255 x 133	75901101	75901201	75901103	75901203