

OLYMPIA LED

IP43

IK05

CLASS
I

C E

A general purpose, surface wall / ceiling mounted LED luminaire with a high luminous efficiency.

FEATURES & BENEFITS

- > Excellent resistance to UV and chemical agents
- > Average rated LED life: >80,000hrs L80/B10 [Ta@ 25°C]
- > Optimum colour consistency - 3 step MacAdam chromaticity tolerance
- > Photobiological hazard: RG0

PERFORMANCE



Light source	LED (Samsung)
LED output	1283 - 2555lm
Luminaire output	900 - 1790lm
CRI	>80
Beam angle	120°

MATERIALS

Body	Sheet steel
Finish	Black (RAL 9005) / White (RAL 9003)
Diffuser	Polycarbonate

OPTIONS

- > 3hr emergency
- > Other RAL finishes



LAMP	COLOUR TEMP	DELIVERED LUMENS	FINISH	STANDARD	DALI	EMERGENCY STANDARD	DALI
8W	3000K	900lm	Black	44100101	44100103	44100191	44100193
8W	4000K	945lm	Black	44100201	44100203	44100291	44100293
11W	3000K	1230lm	Black	44100301	44100303	44100391	44100393
11W	4000K	1295lm	Black	44100401	44100403	44100491	44100493
16W	3000K	1700lm	Black	44100501	44100503	44100591	44100593
16W	4000K	1790lm	Black	44100601	44100603	44100691	44100693
8W	3000K	900lm	White	44100701	44100703	44100791	44100793
8W	4000K	945lm	White	44100801	44100803	44100891	44100893
11W	3000K	1230lm	White	44100901	44100903	44100991	44100993
11W	4000K	1295lm	White	44101001	44101003	44101091	44101093
16W	3000K	1700lm	White	44101101	44101103	44101191	44101193
16W	4000K	1790lm	White	44101201	44101203	44101291	44101293