



IP65 IK06 CLASS I CE

PHOENIX LED

A versatile, energy efficient, IP65 LED wall mounted luminaire that provides direct or direct and indirect illumination.

Suitable for a wide range of architectural, commercial and residential applications.

PHOENIX LED


FEATURES & BENEFITS

- > Various lens options
- > High resistance to UV and oxidation
- > Average rated life: >50,000hrs (L80/B10)
- > Optimum colour consistency - 3 step MacAdam chromaticity tolerance
- > Easy to install and maintain



PERFORMANCE

Light source	LED
Distribution	Symmetric
LED output	1092 - 4440lm (DIR) 2 x 820lm - 2 x 2150 (DI-IN)
Luminaire output	936 - 3662lm (DIR) 2 x 697lm - 2 x 1820lm (DI-IN)
Lumen efficiency	≥94lm/W
CRI	>85
Beam angle	38 degree



10W, 3000K

MATERIALS

Body	Die-cast aluminium EN AB44100
Finish	Anthracite grey / Light grey
Diffuser	3mm soda-lime tempered clear glass
External fixings	Stainless steel A4-70
Wiring	Ø8/12mm cable entry



OPTIONS

- > DALI
- > Second cable entry

LAMP	COLOUR TEMP	DELIVERED LUMENS	DIMENSIONS	DISTRIBUTION	ANTHRACITE GREY	LIGHT GREY
10W	3000K	936lm	180 x 90	DIRECT	75700101	75700201
10W	4000K	1020lm	180 x 90	DIRECT	75700301	75700401
2 x 7W	3000K	2 x 697lm	180 x 90	DIRECT/INDIRECT	75700501	75700601
2 x 7W	4000K	2 x 748lm	180 x 90	DIRECT/INDIRECT	75700701	75700801
32W	3000K	3182lm	240 x 115	DIRECT	75700901	75701001
32W	4000K	3662lm	240 x 115	DIRECT	75701101	75701201
2 x 17W	3000K	2 x 1763lm	240 x 115	DIRECT/INDIRECT	75701301	75701401
2 x 17W	4000K	2 x 1820lm	240 x 115	DIRECT/INDIRECT	75701501	75701601