

POLARIS LED

IP20 CLASS I CE

A general purpose three-circuit track LED luminaire available in multiple outputs, optics and finishes with excellent colour rendering.

FEATURES & BENEFITS

- > 350° rotation in the vertical axis and 90° pivot upwards
- > Average rated LED life: >60,000hrs - (L90/B10) - maintenance free
- > Optimum colour consistency - 3 step MacAdam ellipse tolerance

PERFORMANCE


Light source	LED
LED output	1910 - 3670lm
Luminaire output	1300 - 2540lm
Luminaire efficiency	≥84lm/W
CRI	>80
Beam angle	20° / 45°

MATERIALS

Body	Aluminium
Finish	White / Black
Mounting	Three-circuit track/Surface

OPTIONS

- > CRI>90 for fashion, meat, fish and bread displays
- > Honeycomb optical accessory available



LAMP	COLOUR TEMP	DELIVERED LUMENS	BEAM	TRACK		SURFACE	
				WHITE	BLACK	WHITE	BLACK
15W	3000K	1320lm	20°	26300101	26301301	26302501	26303701
15W	4000K	1360lm	20°	26300201	26301401	26302601	26303801
15W	3000K	1300lm	45°	26300301	26301501	26302701	26303901
15W	4000K	1340lm	45°	26300401	26301601	26302801	26304001
21W	3000K	1810lm	20°	26300501	26301701	26302901	26304101
21W	4000K	1870lm	20°	26300601	26301801	26303001	26304201
21W	3000K	1770lm	45°	26300701	26301901	26303101	26304301
21W	4000K	1830lm	45°	26300801	26302001	26303201	26304401
29W	3000K	2460lm	20°	26300901	26302101	26303301	26304501
29W	4000K	2540lm	20°	26301001	26302201	26303401	26304601
29W	3000K	2410lm	45°	26301101	26302301	26303501	26304701
29W	4000K	2490lm	45°	26301201	26302401	26303601	26304801