



IP69 IK10 950° CLASS I CE

# RENEGADE LED

A vandal-resistant, IP69 tubular LED luminaire, designed for individual or continuous mounting, that offers total protection against dust and water penetration and allows it to be cleaned with pressure jets.

Ideal for a wide range of applications including food processing and industrial installations, warehouses, loading areas, sports centres, stadia, transport terminals, coastal and saline environments.

# RENEGADE LED

## FEATURES & BENEFITS

- > Excellent uniformity and quality of light
- > Non-corrosive
- > Quick connectors for easy installation
- > Average rated LED life: >50,000hrs - maintenance free
- > Optimum colour consistency—3 step MacAdam ellipse tolerance
- > Photobiological risk group RG1

## PERFORMANCE



Light source	LED
LED output	1550 - 6700lm
Luminaire output	1037 - 4481lm
Luminaire efficiency	≥80lm/W
CRI	>80
UGR	<19

## MATERIALS

Body	Polycarbonate
Reflector	High gloss aluminium
End caps	Stainless steel

## OPTIONS

- > 3hr emergency
- > Continuous line joining kit
- > Suspension kit
- > Anti-vandal polycarbonate clamps
- > 3000K



LAMP	COLOUR TEMP	DELIVERED LUMENS	DIMENSIONS	STANDARD	DALI
13W	4000K	1037lm	Ø100 x 763	20802001	20802003
16W	4000K	1786lm	Ø100 x 763	20802101	20802103
24W	4000K	2140lm	Ø100 x 1375	20802201	20802203
32W	4000K	3571lm	Ø100 x 1375	20802301	20802303
29W	4000K	2675lm	Ø100 x 1660	20802401	20802403
40W	4000K	4481lm	Ø100 x 1660	20802501	20802503