

RONDO LED

IP66 IK10⁺ CLASS I
850° CE

FEATURES & BENEFITS

- > Robust design - non-corrosive and abrasion resistant
- > Exceptionally high impact resistance: IK10+ / 120 joules
- > Rip-out resistant skirt - capable of withstanding severe vandalism.
- > Average 50,000h LED life (L80/B50) - no maintenance
- > Optimum colour consistency—3 step MacAdam ellipse tolerance
- > Photobiological hazard: RG0




PERFORMANCE

Light source	LED
Luminaire output	1500 - 2550lm
Luminaire efficiency	≥121lm/W
CRI	>80


MATERIALS

Body	Die-cast aluminium, marine grade
Finish	White (RAL 9016)/Grey (RAL 9006) /
Diffuser	Black (RAL 9005)
External fixings	Opal polycarbonate, 3.5mm thick M5 stainless steel tamper-proof crosshead screws
Wiring	2 x side Ø20.5mm cable entry



OPTIONS

- > 3hr emergency
- > Microwave sensor for enhanced energy savings
- > Bluetooth enabled
- > Flush mounted version
- > Slave version



LAMP	COLOUR TEMP	DELIVERED LUMENS	STANDARD			DALI		
			WHITE	GREY	BLACK	WHITE	GREY	BLACK
12W	3000K	1500lm	43300101	43300301	43300501	43300103	43300303	43300503
12W	4000K	1550lm	43300201	43300401	43300601	43300203	43300403	43300603
17W	3000K	2050lm	43300701	43300901	43301101	43300703	43300903	43301103
17W	4000K	2150lm	43300801	43301001	43301201	43300803	43301003	43301203
20W	3000K	2450lm	43301301	43301501	43301701	43301303	43301503	43301703
20W	4000K	2550lm	43301401	43301601	43301801	43301403	43301603	43301803