



IP65 IK05 CLASS I CE

# SCIROCCO

A high powered, surface mounted or suspended, non-corrosive high bay LED luminaire with deep cooling fins for excellent thermal management.

# SCIROCCO LED


## FEATURES & BENEFITS

- > High-powered LED light source
- > Non-corrosive due to degreasing and phosphochromatizing process
- > High resistance to chemical and atmospheric agents due to degreasing and phosphochromatizing process making it suitable for chlorine environments
- > Fast plug connector - for easy installation
- > Long rated LED life >74,000hrs (L80/B10)
- > Optimum colour consistency—3 step MacAdam
- > Excellent heat sink for effective thermal management
- > Surge protection up to 6/8Kv



## PERFORMANCE

Light source	LED (Samsung)
Light distribution	Symmetric / Asymmetric
LED output	16950 - 28600lm
Luminaire output	14630 - 25170lm
Luminaire efficiency	≥134lm/W
CRI	>80
Beam angle	90° / AS 55°




138W, 4000K, 90°

## MATERIALS

Body	Die-cast aluminium
Finish	Anthracite grey (RAL 7039)
Diffuser	Transparent PMMA anti-UV

## OPTIONS

- > 3hr emergency
- > Wall / Ceiling rotating bracket
- > Protection grid (IK08)
- > 3000K / 5000K
- > CRI>90



LAMP	COLOUR TEMP	DELIVERED LUMENS	DISTRIBUTION	STANDARD	DALI
99W	4000K	14630lm	Asymmetric 55°	71601001	71601003
138W	4000K	18515lm	Asymmetric 55°	71601101	71601103
184W	4000K	24685lm	Asymmetric 55°	71601201	71601203
99W	4000K	14920lm	Symmetric 90°	71601301	71601303
138W	4000K	18880lm	Symmetric 90°	71601401	71601403
184W	4000K	25170lm	Symmetric 90°	71601501	71601503