

SIERRA SURFACE IP LED

IP65 CLASS I CE

FEATURES & BENEFITS

- > Uniform light distribution
- > Various sizes available
- > Average rated LED life: >54,000hrs (L80/B10)
- > Optimum colour consistency - 3 step MacAdam chromaticity tolerance
- > Photobiological hazard: RG1

PERFORMANCE



Light source	LED
LED output	6360 - 14480lm
Luminaire output	3820 - 9560lm
Luminaire efficiency	≥90lm/W
CRI	83

MATERIALS

Body	Sheet steel
Finish	White
Diffuser	Opal polycarbonate TP(a)

OPTIONS

- > 3000K
- > 2 step MacAdam, CRI >90
- > Other lumen outputs available on request
- > Tempered glass / microprism diffuser
- > Tuneable white
- > Internal fuse and LS0H cable



LAMP	COLOUR TEMP	DELIVERED LUMENS	DIMENSIONS	STANDARD	DALI	EMERGENCY	
						STANDARD	DALI
43W	3000K	3990lm	596 x 596	24301301	24301303	24301391	24301393
43W	4000K	4070lm	596 x 596	24301401	24301403	24301491	24301493
43W	3000K	3820lm	296 x 1196	24301501	24301503	24301591	24301593
43W	4000K	3910lm	296 x 1196	24301601	24301603	24301691	24301693
100W	3000K	9380lm	596 x 596	24301701	24301703	24301791	24301793
100W	4000K	9560lm	596 x 596	24301801	24301803	24301891	24301893