

SOFFITE LED



FEATURES & BENEFITS

- > High impact resistance: IK10 / 20 joules
- > Suitable for continuous in-line mounting
- > Discreet surface mounting - 80mm protrusion at 45°
- > Optimum colour consistency—3 step MacAdam ellipse tolerance
- > Average rated LED life: >50,000hrs (L90/B50)
- > Photobiological hazard: RG0

PERFORMANCE


Light source	LED
Distribution	Symmetric
Luminaire output	1330 - 5340lm
Luminaire efficiency	≥111lm/W
CRI	>80

MATERIALS

Body	Aluminium
Finish	White (RAL 9016)
Diffuser	Opal polycarbonate TP(a)
Wiring	Dual entry Ø20.5mm cable for 4 x 1.5mm ² cables

OPTIONS

- > 3hr emergency
- > 3000K
- > Slave configurations
- > Microwave or PIR sensor for enhanced energy savings
- > Bespoke made-to-measure service



LAMP	COLOUR TEMP	DELIVERED LUMENS	DIMENSIONS	STANDARD	DALI
12W	4000K	1330lm	615 x 92 x 92	20900201	20900203
18W	4000K	2270lm	615 x 92 x 92	20900401	20900403
14W	4000K	1680lm	915 x 92 x 92	20900601	20900603
26W	4000K	3250lm	915 x 92 x 92	20900801	20900803
17W	4000K	2350lm	1195 x 92 x 92	20901001	20901003
33W	4000K	4240lm	1195 x 92 x 92	20901201	20901203
26W	4000K	3340lm	1475 x 92 x 92	20901401	20901403
41W	4000K	5340lm	1475 x 92 x 92	20901601	20901603