



IP65 IK06 CLASS I CE

TARAGO LED

A versatile, energy efficient, IP65 LED projector luminaire that provides direct or direct and indirect illumination.

Suitable for a wide range of architectural, commercial and residential applications.

TARAGO LED

FEATURES & BENEFITS

- > Various lens options
- > High resistance to UV and oxidation
- > Optimum colour consistency - 3 step MacAdam tolerance
- > Easy to install and maintain
- > Average rated LED life: >50,000hrs (L80/B10)

PERFORMANCE





Light source	LED
Distribution	Symmetric
Emission	Direct / Direct & indirect
Luminaire output	1267 - 3666lm (DIR) 2 x 1269 - 2 x 2543 (DI-IN)
CRI	>90
Beam angle	14° - 71°

MATERIALS

Body	Extruded aluminium EN AB44100
Finish	Anthracite grey / Light grey
Diffuser	Stainless steel A4-70
External fittings	4mm soda-lime tempered clear glass
Wiring	M12 IP67 cable gland

OPTIONS

- > DALI
- > Coloured films



TARAGO LED

DIRECT ILLUMINATION

LAMP	COLOUR TEMP	DELIVERED LUMENS	BEAM	DIMENSIONS	STANDARD ANTHRACITE GREY	LIGHT GREY
12W	3000K	1267lm	32°	125 x 90 x 90	71810001	71810101
12W	4000K	1312lm	32°	125 x 90 x 90	71810201	71810301
16W	3000K	1760lm	14°	204 x 125 x 125	71810801	71810901
16W	4000K	1814lm	14°	204 x 125 x 125	71811001	71811101
16W	3000K	1581lm	35°	204 x 125 x 125	71811201	71811301
16W	4000K	1630lm	35°	204 x 125 x 125	71811401	71811501
26W	3000K	2464lm	28°	280 x 200 x 200	71812401	71812501
26W	4000K	2536lm	28°	280 x 200 x 200	71812601	71812701
26W	3000K	2470lm	71°	280 x 200 x 200	71812801	71812901
26W	4000K	2543lm	71°	280 x 200 x 200	71813001	71813101
39W	3000K	3542lm	28°	280 x 200 x 200	71813201	71813301
39W	4000K	3657lm	28°	280 x 200 x 200	71813401	71813501
39W	3000K	3551lm	71°	280 x 200 x 200	71813601	71813701
39W	4000K	3666lm	71°	280 x 200 x 200	71813801	71813901

DIRECT & INDIRECT ILLUMINATION

LAMP	COLOUR TEMP	DELIVERED LUMENS	BEAM	DIMENSIONS	STANDARD ANTHRACITE GREY	LIGHT GREY
24W	3000K	2 x 1267lm	32°	125 x 90 x 90	71810401	71810501
24W	4000K	2 x 1312lm	32°	125 x 90 x 90	71810601	71810701
32W	3000K	2 x 1760lm	14°	204 x 125 x 125	71811601	71811701
32W	4000K	2 x 1814lm	14°	204 x 125 x 125	71811801	71811901
32W	3000K	2 x 1581lm	35°	204 x 125 x 125	71812001	71812101
32W	4000K	2 x 1630lm	35°	204 x 125 x 125	71812201	71812301
52W	3000K	2 x 2464lm	28°	280 x 200 x 200	71814001	71814101
52W	4000K	2 x 2536lm	28°	280 x 200 x 200	71814201	71814301
52W	3000K	2 x 2470lm	71°	280 x 200 x 200	71814401	71814501
52W	4000K	2 x 2543lm	71°	280 x 200 x 200	71814601	71814701