

TUBO LED

IP44

CLASS
I

C E

FEATURES & BENEFITS

- > High efficiency, general purpose surface LED downlight
- > Long average LED life >60,000hrs LED life (L90/B10)
- > Optimum colour consistency - 3 step MacAdam chromaticity tolerance
- > Matching LED pendant available in the same range

PERFORMANCE


Light source	LED
LED output	1760 - 3250lm
Luminaire output	1420 - 2640lm
Luminaire efficiency	≥88lm/W
CRI	80
Beam angle	30° / 50°

MATERIALS


Body	Extruded aluminium
Finish	Anthracite grey / White / Black
Diffuser	Clear PMMA

OPTIONS

- > 3hr emergency
- > 70 degree beam
- > Other RAL colours on request



15W, 3000K



LAMP	COLOUR TEMP	DELIVERED LUMENS	BEAM	STANDARD			DALI		
				GREY	WHITE	BLACK	GREY	WHITE	BLACK
15W	3000K	1420lm	30°	31900101	31901901	31903501	31900103	31901903	31903503
15W	4000K	1460lm	30°	31900201	31902001	31903601	31900203	31902003	31903603
15W	3000K	1430lm	50°	31900301	31902101	31903701	31900303	31902103	31903703
15W	4000K	1470lm	50°	31900401	31902201	31903801	31900403	31902203	31903803
21W	3000K	1960lm	30°	31900701	31902501	31904101	31900703	31902503	31904103
21W	4000K	2020lm	30°	31900801	31902601	31904201	31900803	31902603	31904203
21W	3000K	1970lm	50°	31900901	31902701	31904301	31900903	31902703	31904303
21W	4000K	2030lm	50°	31901001	31902801	31904401	31901003	31902803	31904403
29W	3000K	2550lm	30°	31901301	31903101	31904701	31901303	31903103	31904703
29W	4000K	2630lm	30°	31901401	31903201	31904801	31901403	31903203	31904803
29W	3000K	2560lm	50°	31901501	31903301	31904901	31901503	31903303	31904903
29W	4000K	2640lm	50°	31901601	31903401	31905001	31901603	31903403	31905003