

TUBO SURFACE IP65

IP65

CLASS
I

C E

An architectural ceiling-mounted cylindrical LED luminaire available in multiple beam angles and finishes for design flexibility. Suitable for use indoors and outdoors.

FEATURES & BENEFITS

- > Elegant design with clean, smooth lines
- > Average 60,000hr LED life (L90/B10)
- > Optimum colour consistency - 3 step MacAdam ellipse tolerance

PERFORMANCE

Light source	LED
Luminaire output	1330 - 2640lm
CRI	>80
Beam angle	30° / 50° / 70°

MATERIALS

Body	Extruded aluminium
Finish	Anthracite grey / White / Black
Diffuser	Clear tempered glass

OPTIONS

- > DALI
- > 3hr emergency



LAMP	COLOUR TEMP	DELIVERED LUMENS	BEAM	ANTHRACITE GREY	WHITE	BLACK
15W	3000K	1420lm	30°	32100101	32101901	32103701
15W	4000K	1460lm	30°	32100201	32102001	32103801
15W	3000K	1430lm	50°	32100301	32102101	32103901
15W	4000K	1470lm	50°	32100401	32102201	32104001
15W	3000K	1330lm	70°	32100501	32102301	32104101
15W	4000K	1370lm	70°	32100601	32102401	32104201
21W	3000K	1960lm	30°	32100701	32102501	32104301
21W	4000K	2020lm	30°	32100801	32102601	32104401
21W	3000K	1970lm	50°	32100901	32102701	32104501
21W	4000K	2030lm	50°	32101001	32102801	32104601
21W	3000K	1830lm	70°	32101101	32102901	32104701
21W	4000K	1890lm	70°	32101201	32103001	32104801
29W	3000K	2550lm	30°	32101301	32103101	32104901
29W	4000K	2630lm	30°	32101401	32103201	32105001

TUBO SURFACE IP65

LAMP	COLOUR TEMP	DELIVERED LUMENS	BEAM	ANTHRACITE GREY	WHITE	BLACK
29W	3000K	2560lm	50°	32101501	32103301	32105101
29W	4000K	2640lm	50°	32101601	32103401	32105201
29W	3000K	2390lm	70°	32101701	32103501	32105301
29W	4000K	2460lm	70°	32101801	32103601	32105401

